## **VeDiS-II Specification**





## For MAZDA® 1990 - 2003

Version: V2011.01 Date: Jan. 2011

CVCTEM		VEAD	DATA CTDEAM	DEAD CODE	CLEAD CODE	CWITCH TEST
SYSTEM		YEAR	DATA STREAM	READ CODE	CLEAR CODE	SWITCH TEST
РСМ	Engine	1996 – 2005 (NOTE)	<b>✓</b>	<b>~</b>	<b>✓</b>	
	AT	1996 – 2005 (NOTE)	•	<b>~</b>	•	
Engine (Impulse code)		1990 – 2002		<b>~</b>	<b>✓</b>	<b>✓</b>
TCM / AT (Impulse code)		1990 – 2002		<b>~</b>	•	
Air Bag		From prod. up to 2002		<b>~</b>	<b>✓</b>	
ABS		From prod. up to 2002		<b>~</b>	•	
Cruise Control		From prod. up to 2002		<b>~</b>	•	
A/C		From prod. up to 2002		<b>~</b>	<b>✓</b>	

## **Connectors and Systems:**

6+1 Pin Connector:	PCM (Engine)
20 Pin Connector:	PCM (Engine)
	TCM (Automatic Transmission)
17+8 Pin Connector:	PCM (Engine)
	TCM (Automatic Transmission)
	ABS
	Air Bag
OBD-II Connector:	Powertrain Systems adopt ISO 9141-2, and ISO 14230 protocols for communication.
OBD-II Connector:	MAZDA US Models from 1995~2000, are equipped with 17+8 Pin and OBD-II Connectors and it have to test with 17+8Pin Connector. OBD-II Connector only supports Generic OBD-II protocol communication only.
	MAZDA from year 2000 begin equipped with OBD-II Connector only.

<sup>\*</sup> NOTE: The system adapted with CAN protocol is not supported.

The information contained herein is the exclusive property of Autoland Scientech® and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of Autoland Scientech®. Autoland Scientech® reserve the right to make any change without notice. The trademarks mentioned belong to the owners.